



SMARTFOX®

SMARTFOX

Pro Heater 3 / 4.5 / 6 / 9K

Technical data sheet

Power to Heat: The SMARTFOX Pro Heater 3 / 4.5 / 6 / 9K is the ideal addition to your SMARTFOX energy manager and stores PV surplus in 15 dynamic stages as hot water.


The "Heater" can be used to heat heating and drinking water in enameled buffer tanks and containers. The integrated temperature sensor can be used to ensure sufficient hot water even in bad weather and to perform a hygiene function (legionella).

The included performance measurement enables high-resolution monitoring via web portal & APP.

With the remote control, you always have your hot water under control, even when you're on the move.

Compatible with all SMARTFOX energy managers!

Control and safety
thermostat



Product information


Technical data

Art. No.	0796554799001	0796554799018	0767523866338	0796554799025
Heating capacity max.	3kW	4.5kW	6kW	9kW
Heat output min.	110W	165W	220W	333W
Switching steps	15 *Power of the steps varies according to model			
Tension	3~400V, 50Hz			
Rated current	max. 4.41A	max. 6.62A	max. 8.82A	max. 12.99A
Protection	LS 3B13	LS 3B13	LS 3B13	LS 3B13
Standby consumption	3-4W			
Screw head				
Screw-in thread (AG)	G 1 1/2" (6/4")			
Width across flats	SW60 (DIN ISO 228)			
material	brass			
Operating pressure	max. 10bar			
Hea body ting				
Immersion depth	345mm	360mm	480mm	660mm
Unheated length	100mm			
Sheath material	2.4858 - Alloy 825			
Surface load	10W/cm ²			
Continuous operation suitability	Yes			
Galvanic isolation	Yes (use in glass-lined containers possible)			
Area of application	Hot water boiler & buffer tank (suitable for drinking water)			
Installation	horizontal			
Connection housing				
material	PC + ABS (UL 94 V0)			
Protection class	IP54			
Electrical connection	Plug 5-pin nominal cross-section 1.5mm ² incl. connection cable 5m			
Communication connection	Plug 5-pin nominal cross-section 0.5mm ² (min. 0.4mm ² / max. 0.75mm ²) incl. Connection cable 5m			
Interfaces	RS485 (4-20mA coming soon)			
RS485 addressing	Parameters via DIP switch			
Temperature sensor	integrated (class B)			


Temperature control

Type	Temp. controller (TR) + safety temp. limiter (STB)			
Control temperature (TR)	10-80°C			
Switch-off temperature (STB)	93°C			
Display	Status display via LED			
Measuring unit	Power measurement included			
Dimensions incl. plug	W 135mm x H 189mm x L			
W x H x L	L 468mm	L 483mm	L 603mm	L 783mm
Weight	1607g	1754g	1920g	2203g
Temperature range (in operation)	Ambient temperature 10-45°C			
Humidity (during operation)	5-95% non-condensing			
Operating mode	With energy manager: 15-stage surplus control, minimum temperature maintenance, weekly timer, hygiene function frost protection & fixed temperature... Stand-alone operation: frost protection & fixed temperature possible			
Compatible energy managers (RS485)	SMARTFOX Pro & SMARTFOX Pro 2			
Compatible energy managers (4-20mA)	All SMARTFOX energy managers <small>*Not all functions available</small>			
Remote control	Via SMARTFOX energy manager (my.smartfox.at & APP)			
Monitoring	Via SMARTFOX energy manager (my.smartfox.at & APP)			
Certificates, standards	CE, EN 14597, EN IEC 60730-2-9, EN 60335-2-21, EN 60335-1			

Function overview



Dimensions



*The scale refers to the SMARTFOX Pro Heater 6K. The screw-in and total lengths of the product variations are indicated accordingly



smartfox.at/downloads

Austria / Europe

Head office:

DAfi GmbH | Niedernfritzerstraße 120
5531 Eben im Pongau | AUSTRIA

Tel +43 (0)720 302 555
mail support@smartfox.at
Web www.smartfox.at

Germany

Branch DE:

SMARTFOX GmbH | Wankelstraße 40
50996 Cologne | GERMANY

Tel +49 (0)2236 48095-00
mail technik@smartfox.de
Web www.smartfox.de